product details

64702 ECO 400W 240V R7S FS1

Product description:	64702 ECO 400W 240V R7S FS1
Product code:	4008321275646
Quantity:	Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:
http://catalog.myosram.com?~language=EN&~country=COM&it_p=4008321275646

Applications	
Dimmable	Yes
Burning position	any
Fuse, quick-acting	2.0 A

Categorizations	
ILCOS	HDG-400-240-R7s-114,2

Certificates & Standards	
EEI - Energy Label	C

General Description	
Base (standard designation)	R7s
Mercury-free	Yes
Lamp mercury content	0.0 mg

Technical - Electrical Data	
Nominal wattage	400 W
Rated wattage	400 W
Claimed equivalent incand. lamp power	500 W
Nominal voltage (product)	240 V
Rated number of switching cycles	1000000
Rated power factor λ	1.00

Technical - Geometries	
Overall length	114.20 mm
Contact spacing	114.2 mm
Diameter	12.00 mm
Length	119.60 mm

Technical - Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h

Technical - Light Technical Data	
Rated color rendering index (Ra)	100
Luminous flux	9000 lm
Nominal luminous flux	9000 lm
Rated luminous flux	9000 lm
Lumen main.fact.at end of nom.life time	0.80
Color temperature	2950 K
Rated color temperature	3000 K
Color rendering index Ra	100

Subject to change without notice. Errors and omission excepted.
© 2010 OSRAM GmbH

product details

64702 ECO 400W 240V R7S FS1

Technical - Light Technical Data	
Rated warm-up time (60 %)	0 s
Rated starting time	0.0 s

Packaging units

Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4008321275646	Folding carton box contains 1 Piece	21,000 mm x 18,000 mm x 126,000 mm	15,000 g (0,000 g)	0,048 Cubic dec.
4008321275653	Shipping carton box contains 20 Piece	112,000 mm x 77,000 mm x 137,000 mm	342,000 g (0,000 g)	1,181 Cubic dec.

HALOLINE ECO from OSRAM is the classic lamp for small outdoor systems for floodlighting buildings and sports arenas and for security lighting. It is also experiencing a renaissance in the home. In addition to providing indirect lighting, innovative pendant luminaires are re-conquering classic applications, providing wide-area lighting in a wide range of new and exciting designs.

- Brilliant ECO accent lighting
- Direct replacement for standard tubular halogen lamps
- Significantly lower CO2 emissions
- Lower thermal output (compared with the standard reference product)
- Ideal for emphasizing and accentuating the structure of a room
- No transformer required
- Average life: 2,000 h
- Dimmable
- R_a=100
- Color temperature: 48 W/80 W/120 W short - 2,900 K; 120 W long/160 W/230 W/400 W - 2,950 K
- Design: 74.9 mm (48 W, 80 W 120 W short); 114.2 mm (120 W long, 160 W, 230 W, 400 W)
- Base: R7s

Subject to change without notice. Errors and omission excepted.
© 2010 OSRAM GmbH